





ezoBord Work Zone Dividers add privacy, color and style, ezoBord Work Zone Dividers are cut in various shapes making every office space a better place to work in.

Divide space, absorb sound and create visual privacy all in and cost effectively. one simple solution...

ezoBord Work Zone Dividers are cut in various shapes and patterns ranging from organic shapes to geometric shapes to cityscapes. A great way to define space quickly and cost effectively.

Made with recycled plastic water bottles.

WORK ZONE DIVIDERS


WORK ZONE DIVIDERS

AZTEC


BAMBOO

i i


BUBBLE



CHEVRON




CIRCLES




WIDTH HEIGHT THICKNESS 471/2" (1207mm) 95" (2413mm) 3/8" (9mm) 471/2" (1207mm) 95" (2413mm) 1/2" (12mm)


CUBE



DAIRE




DECO



DOKUMA






WIDTH HEIGHT THICKNESS 471/2" (1207mm) 95" (2413mm) 3/8" (9mm) 471/2" (1207mm) 95" (2413mm) 1/2" (12mm)

WORK ZONE DIVIDERS


WORK ZONE DIVIDERS

FLATLINE


GALAXY




KESIK



LAZER



LEAF




WIDTH HEIGHT THICKNESS 471/2" (1207mm) 95" (2413mm) 3/8" (9mm) 471/2" (1207mm) 95" (2413mm) 1/2" (12mm)


ORMAN




PIXELATED CIRCLES



PIXELATED SQUARES



SQUARES




WIDTH HEIGHT THICKNESS

471/2" (1207mm) 95" (2413mm) 3/8" (9mm)

471/2" (1207mm) 95" (2413mm) ½" (12mm)

SPECIFICATIONS

WORK ZONE DIVIDER



PATTERNS

20 standard patterns available.

47.5" (1207mm) × 95" (2413mm) SIZE

THICKNESS 3/8" (9mm) | ±0.5mm

1/2" (12mm) | ±0.5mm

COMPOSITION

100% PET (min. %50 recycled content)

PRODUCT VARIANCES

Variation in fiber mix and colour may occur. All products will be supplied within commercial tolerances.

CLEANING

Remove dust and dirt with a stiff plastic bristle brush. Distilled water can be used to remove stains. Always use a soft, clean cloth and blot dry. Vacuuming works great as well.

FIRE TESTING **NORTH AMERICA:**

- · ASTM E-84 Class A*
- CAN ULC S102-10

EUROPE AND UK:

· EN13501-1: 2007

* Upon request, 1/2"(12mm) sheet material is treated with USA origin post-production flame retardant to Class A surface burning characteristics. Post sheet production FR treatment does not contain any Red List Restricted Chemicals and complies with California Proposition 65. Contact customer service for technical information, test data and safety data sheets for flame retardant

ACOUSTICS

Refer to ASTM C423 test chart for specific absorption rates/frequency.

- 3/8" (9mm): NRC 0.75 (subject to mounting conditions and geometrical properties)
- \cdot ½" (12mm): NRC 0.85 (subject to mounting conditions and geometrical properties)

(subject to mounting conditions and geometrical properties)

ENVIRONMENT

Made of polyester fiber, min. 50% of which comes from recycled water bottles which contributes to LEED MR Credit and BREEAM Health and Wellbeing, Materials points due to recycled content, acoustic performance, and low emitting materials. No VOC's: CDPH v1.2 and REACH SVHC Compliant.

USGBC LEED V4 CREDITS

While individual products do not 'earn' LEED credits, ezoBord can contribute to the following LEED v4 Credits. Please refer to the USGBC LEED credit guides for detailed requirements.

- · EQc9 for enhancing acoustic performance
- · MRc3 BPDO for sourcing of raw materials for recycled
- EQc6 interior lighting for surface reflectance (lighter color options).


NOISE REDUCTION - 3/8" (9MM)

Constructed from 3/8" (9mm) ezoBord Divider Pattern

Galaxy

SOUND ABSORPTION COEFFICIENTS (ASTM C423-17)

NRC SAA 125 250 500 1000 2000 4000 0.60 0.61 0.37 0.43 0.50 0.65 0.85 0.98









COLOR & FINISHES

COLORS 3/8" (9MM)



COLORS 1/2" (12MM)





ENVIRONMENT

Our Commitment to the Environment

There are approximately 50 billion water bottles consumed around the world each year, and only about half of those get recycled. The rest end up in landfills, littered through our neighborhoods, or floating in our oceans.

Bottled water consumption has more than doubled since 2000; in 2015 there was the equivalent of more than 5 bottles of water consumed for every person in the USA every single week. This, of course, means that the amount of oil required to produce the energy used for the water bottling process continues to grow.

In 2007, the last year global statistics of oil consumption were available, between 32 million and 54 million barrels of oil were used to produce the bottled water that was consumed in the USA alone. This energy is used to make the bottles from PET pellets (1 million tons in the USA), treat water, bottle the water, label the bottles, and transport the bottled water. Most of the energy consumption occurs in the creation of the bottles themselves. To help in the lifecycle of this plastic product, we have chosen to manufacture our material so that it recycles these PET bottles. We are doing our part to reduce the waste. This acoustical and tackable material is made from PET bottles in a zero-waste process with postindustrial recycling. An environmentally friendly, sustainable, and waste reduced alternative to traditional acoustical/tackable material that looks great in any office, education, or open space installation.

ezoBord is




- · low VOC
- · formaldehyde free

DID YOU KNOW...



For every pound of recycled PET bottles (approximately 23) energy use is reduced by 84% and greenhouse gas emissions are reduced by 71%.

± 166 PET BOTTLES



are used to make one 9mm thick ezoBord sheet





EZOBORD UK LIMITED

Unit 20 Westwood Business Park Margate, Kent CT9 4JJ

Customer Care

customercare@ezobord.co.uk P: 01843 6661 International: +44 1843 666111

Sales

sales@ezobord.co.uk P: 01843 204027 International: +44 1843 204027

ezoBord Head Office

6845 Rexwood Road, Unit 7 Mississauga, ON L4V 1S5 Canada FAX +1 416 665 3571 info@ezobord.com

FOLLOW US







ezobord.com